

Material Safety Data Sheet (MSDS)- Mixed Glycol

Company name : Loki Industries

1. Identification:

- Chemical Name: Mixed Glycol
- CAS Number: Mixture
- Synonyms: Glycol Blend, Industrial Glycol
- Uses: Solvent, antifreeze, coolant, industrial applications

2. Hazard Identification:

- Hazard Class: May be harmful if inhaled or swallowed
- Health Hazards: May cause skin irritation, dizziness, and organ damage with prolonged exposure
- Precautionary Measures: Use protective gloves and ensure proper ventilation

3. Composition/Information on Ingredients:

- Chemical Formula: Blend of glycols
- Concentration: Variable

4. First-Aid Measures:

- Inhalation: Move to fresh air; seek medical attention if symptoms persist
- Skin Contact: Wash with soap and water
- Eye Contact: Rinse cautiously with water for several minutes
- Ingestion: Do not induce vomiting; seek medical help

5. Fire-Fighting Measures:

- Extinguishing Media: Water spray, dry chemical, CO₂
- Hazards: May form hazardous decomposition products when heated
- Protection: Wear self-contained breathing apparatus (SCBA)

6. Accidental Release Measures:

- Personal Protection: Wear gloves, goggles, and protective clothing
- Spill Response: Absorb with inert material; ventilate area

7. Handling and Storage:

- Handling: Use in well-ventilated areas; avoid prolonged exposure.
- Storage: Keep in a cool, dry place in a tightly closed container.

Contact Information:

Loki Industries

Email: lokiind9@gmail.com

Phone: +91 99259 21925

